
django-project-skeleton Documentation

Release 1.3

Mischback

Feb 05, 2018

Contents

1	Notable Features	3
2	Contents	5
2.1	Quickstart	5
2.2	Project Structure	6
2.3	Settings	9
2.4	Apache2 Virtual Host Configuration	12
2.5	Versions	14
3	Hall of Fame	17

django-project-skeleton is my skeleton for Django projects. It provides a directory structure for Django projects during development and deployment. This structure is based on research and own experience of developing Django apps.

Please note: This is *my* skeleton and is developed to fit my very own needs for new Django projects. Please feel free to modify it to your own requirements but be aware that no changes will be made, that **I** do not consider usefull.

Additional note: As of this writing, Django 1.11 is used. So I can only guarantee that this is working with this version.

CHAPTER 1

Notable Features

- prepared directory structure
- modular settings with sane default values
- prepared sample configuration for *Apache2*-deployment with *mod_wsgi*
- including *.gitignore*-files to help getting started with *Git*

2.1 Quickstart

I assume you know what you are doing, so let's just do it:

```
$ django-admin startproject --template=https://github.com/Mischback/django-project-  
↪ skeleton/archive/master.zip [projectname]
```

Your project will look like this:

```
[projectname]/  
├── [projectname]/  
│   ├── __init__.py  
│   ├── settings/  
│   │   ├── common.py  
│   │   ├── development.py  
│   │   ├── i18n.py  
│   │   ├── __init__.py  
│   │   └── production.py  
│   ├── urls.py  
│   └── wsgi.py  
├── apps/  
│   └── __init__.py  
├── configs/  
│   ├── apache2_vhost.sample  
│   └── README  
├── doc/  
│   ├── Makefile  
│   └── source/  
│       └── *snap*  
├── manage.py  
├── README.rst  
├── run/  
│   └── media/  
│       └── README
```



See *Project Structure* for a detailed description of this layout.

2.2 Project Structure

The *normal* Django workflow, as it is described in the official [Django tutorial](#) starts a project with the command:

```
$ django-admin startproject [projectname]
```

Your project will look like this:

```

[projectname]/
├── [projectname]/
│   ├── __init__.py
│   ├── settings.py
│   ├── urls.py
│   └── wsgi.py
└── manage.py

```

However, the `startproject`-command takes an optional argument `template` which can be used to specify a project template to be used for project creation (see [‘Django documentation <https://docs.djangoproject.com/en/1.11/ref/django-admin/#startproject’](https://docs.djangoproject.com/en/1.11/ref/django-admin/#startproject)).

The `template`-argument works with paths on your local machine, but also supports URLs. So you can easily fetch this skeleton from [GitHub](#) using this command:

```
$ django-admin startproject --template=https://github.com/Mischback/django-project-
↪skeleton/archive/master.zip [projectname]
```

Your project will look like this:

```

[projectname]/                                <- project root
├── [projectname]/                            <- Django root
│   ├── __init__.py
│   ├── settings/
│   │   ├── common.py
│   │   ├── development.py
│   │   ├── il8n.py
│   │   ├── __init__.py
│   │   └── production.py
│   ├── urls.py
│   └── wsgi.py
├── apps/
│   └── __init__.py
├── configs/
└── apache2_vhost.sample

```

```

├── README
├── doc/
│   ├── Makefile
│   └── source/
│       └── *snap*
├── manage.py
├── README.rst
├── run/
│   ├── media/
│   │   └── README
│   ├── README
│   └── static/
│       └── README
├── static/
│   └── README
├── templates/
│   ├── base.html
│   ├── core
│   │   └── login.html
│   └── README

```

2.2.1 Django Root

```

[projectname]/                                <- project root
├── [projectname]/                            <- Django root
│   ├── __init__.py
│   ├── settings/
│   │   ├── common.py
│   │   ├── development.py
│   │   ├── i18n.py
│   │   ├── __init__.py
│   │   └── production.py
│   ├── urls.py
│   └── wsgi.py
└── *snap*

```

The Django root directory will be named according to the project name you specified in `django-admin startproject [projectname]`. This directory is the project's connection with Django.

[projectname]/settings/ Instead of a plain *settings*-file, the configuration is split into several files in this Python module. For an in-depth documentation of these settings see [Settings](#).

[projectname]/urls.py The root URL configuration of the project. The only configured set of urls is the admin-application. For background information see [The Django Book Chapter 3](#) and [The Django Book Chapter 8](#).

[projectname]/wsgi.py Deploying Django makes use of WSGI, the Pythonic way of deploying web applications. See the [official settings documentation on WSGI](#) for more details. The default WSGI-application is modified to use our `settings`-module.

2.2.2 apps/

```

[projectname]/                                <- project root
├── *snap*
└── apps/

```

```
└─ __init__.py
└─ *snap*
```

This directory is used for custom applications. You can safely remove this directory, if you do not plan to develop custom applications. Most of a Django project's apps will be installed into the Python path and not be kept in your project root.

2.2.3 configs/

This directory contains configuration files for deployment. Now only a configuration file for deployment with **Apache2** and **mod_wsgi** is provided.

```
[projectname]/          <- project root
└─ *snap*
└─ configs/
    └─ apache2_vhost.sample
        └─ README
└─ *snap*
```

Please note: It is strongly advised to keep your actual server configuration private. Therefore a `.gitignore`-file is provided, which will only include files ending with the suffix `.sample` into *Git*.

For a brief overview of the `configs/apache2_vhost.sample` refer to [Apache2 Virtual Host Configuration](#).

2.2.4 doc/

```
[projectname]/          <- project root
└─ *snap*
└─ doc/
    └─ Makefile
        └─ source/
            └─ *snap*
└─ *snap*
```

This directory contains the source files for this documentation.

You can safely remove this directory, if you just want to use the skeleton for your own project.

2.2.5 run/

```
[projectname]/          <- project root
└─ *snap*
└─ run/
    └─ media/
        └─ README
    └─ README
    └─ static/
        └─ README
└─ *snap*
```

This directory contains necessary files for running Django. All these files may contain sensible or useless information, so you will not want to keep this files in version control. A `.gitignore`-file is prepared.

This directory will contain the SQLite database file (if you keep the provided `dev-settings`) and the `SECRET_KEY` of Django. For a detailed explanation see [Settings](#).

run/media/ Django uses a special folder to store user-provided files (uploads). In the settings-module of this skeleton this directory is set as `MEDIA_ROOT`.

run/static/ Similar to media files, all static assets (i.e. stylesheets, javascript files, images) are served from a special directory.

2.2.6 static/ and templates/

```
[projectname]/          <- project root
├── *snap*
├── static/
│   └── README
├── templates/
│   ├── base.html
│   ├── core
│   │   └── login.html
│   └── README
```

These directories are used for project wide files, meaning project wide static assets and templates.

static/ This directory is used to provide our project wide static assets. Please refer to [the Django documentation](#) for more details. [Settings](#) documents the `STATICFILES_DIRS`-setting.

templates/ This directory is used to provide our project wide templates. [Settings](#) documents the `TEMPLATE_DIRS`-setting. Please note, that there are two basic templates already included. These are used to enable a very basic login functionality for the project.

2.3 Settings

2.3.1 common.py

This file contains settings which are shared between development- and production-settings. They provide sane defaults for developing and a solid base for production settings.

Path Configuration

DJANGO_ROOT Absolute path of the projects Django directory

PROJECT_ROOT Absolute path of the project directory

SITE_NAME The name of our project

STATIC_ROOT The directory to collect static files into. It will be set to `[project_root]/run/static`. Please refer to the [official settings documentation on STATIC_ROOT](#) and [this howto on static files](#).

MEDIA_ROOT The directory for user-uploaded files. It will be set to `[project_root]/run/media`. Please refer to the [official settings documentation on MEDIA_ROOT](#).

STATICFILES_DIRS Django will look in these locations for additional static assets to collect. Our settings module adds `[project_root]/static` to the list. See the [official settings documentation on STATICFILES_DIRS](#) for more details.

PROJECT_TEMPLATES Django will look in these locations for additional templates. Our settings module adds `[project_root]/templates`.

This setting was changed to reflect the changes in Django 1.8: Django features the possibility to use multiple different template engines. This is controlled with the `TEMPLATES` directive and represents the old `TEMPLATE_DIRS` directive. See the [official settings documentation on `TEMPLATE_DIRS`](#) for more details.

Application Configuration

DEFAULT_APPS These are the default apps of `django-admin startproject`. Please note that this is no official setting. Django operates with `INSTALLED_APPS`, which will be set in `dev.py`.

MIDDLEWARE (*new in 1.2; Django 1.10*) These are the default middleware classes, directly taken from the default settings created by `django-admin startproject`. See the [official settings documentation on `MIDDLEWARE_CLASSES`](#) for more details. (Please note: This was used to be called `MIDDLEWARE_CLASSES`)

TEMPLATES This setting reflects the new feature of multiple template engines, which was introduced in Django 1.8. The value is taken from the [official upgrading guide](#) and adjusted to include our project templates, defined in `PROJECT_TEMPLATES`.

Security Configuration

SECRET_FILE Django uses a `SECRET_KEY` for security purposes. As you can clearly see, this is a very sensitive information. We will store this key in a file. This file's location is set up here. Default value is `[project_root]/run/SECRET.key`.

ADMINS You will have to fill this setting yourself, please refer to [official settings documentation on `ADMINS`](#).

MANAGERS You will have to fill this setting yourself, please refer to [official settings documentation on `MANAGERS`](#).

Django Running Configuration

WSGI_APPLICATION This setting determines the path to the WSGI-application. We'll use the default one, so this setting is set to `[project_name].wsgi.application`.

ROOT_URLCONF Determines the root URLconf. Set to `[project_name].urls`. See [official settings documentation on `ROOT_URLCONF`](#).

SITE_ID (*removed in 1.2*) A unique ID of the site. See [official settings documentation on `SITE_ID`](#).

STATIC_URL Determines, under which URL static files are served. You will want to adjust this in a production scenario. Our default value is `/static/`. See [official settings documentation on `STATIC_URL`](#).

MEDIA_URL Determines, under which URL media files are served. You will want to adjust this in a production scenario. Our default value is `/media/`. See [official settings documentation on `MEDIA_URL`](#).

Debug Configuration

DEBUG Activates debugging. In this file, this is set to `False`, because these are our common settings, which are shared between all configurations. We just want debugging while we are developing, so debugging will be activated in `dev.py`. See [official settings documentation on `DEBUG`](#) for additional information.

Internationalization

LANGUAGE_CODE *(removed in 1.3)*

TIME_ZONE *(removed in 1.3)*

USE_I18N *(modified in 1.2: False)* The setting is activated in `i18n.py`.

USE_L10N *(removed in 1.3)*

USE_TZ *(removed in 1.3)*

2.3.2 development.py

(modified in 1.2: renamed `dev.py` to `development.py`) This file contains development settings. Please note, that `manage.py` will now automatically use this setting-file as its default, while `wsgi.py` still refers to `production.py`.

Debug Configuration

DEBUG We are developing, so activate debugging.

ALLOWED_HOSTS *(new in 1.2)* Allow all hostnames to be used to access the server/project. See [official settings documentation on ALLOWED_HOSTS](#).

LOGIN_URL *(new in 1.3)* The URL of Django's built-in login view. See [official settings documentation on LOGIN_URL](#).

LOGIN_REDIRECT_URL *(new in 1.3)* Django will redirect the user to this URL after login, if no specific URL is given. See [official settings documentation on LOGIN_REDIRECT_URL](#).

LOGOUT_REDIRECT_URL *(new in 1.3)* Django will redirect the user to this URL after logout, if no specific URL is given. See [official settings documentation on LOGIN_REDIRECT_URL](#).

Database Configuration

DATABASES I use SQLite for development. The database file will be created in `[project_root]/run/dev.sqlite3`.

Application Configuration

INSTALLED_APPS We have set the default apps. Now we build the (required) `INSTALLED_APPS`-setting by using `DEFAULT_APPS` and add any app we need for development.

2.3.3 i18n.py

(created in 1.3) This file contains all settings, that affect internationalisation (`i18n`). These settings were taken from other parts of the configuration (see `common.py`). The `LocaleMiddleware` will automatically be inserted into the `MIDDLEWARE` list.

The `i18n`-settings are not included by default. They have to be imported in `development.py` or `production.py`.

LANGUAGE_CODE This is the default language of your project. Django will fall back to this language, if the localization-middleware can't determine the user's preferred language. See [official settings documentation on LANGUAGE_CODE](#).

TIME_ZONE Sets the time zone of this project. See [official settings documentation on TIME_ZONE](#).

USE_I18N Activates Django's translation system. See [official settings documentation on USE_I18N](#).

USE_L10N Activates Django's localization engine. See [official settings documentation on USE_L10N](#).

USE_TZ Make datetimes timezone aware. See [official settings documentation on USE_TZ](#).

LANGUAGES A list of supported languages. Django will only provide translation for these. See [official settings documentation on LANGUAGES](#).

LOCALE_PATHS A list of file system locations, to look for translations. See [official settings documentation on LOCALE_PATHS](#). Please note: Django's `LocaleMiddleware` will automatically look for translation files in each apps `locale` directory, so they don't need to be added here.

2.3.4 production.py

(modified in 1.2) This file should contain production settings. Currently, it just reverts some development specific configuration values, `DEBUG` and `ALLOWED_HOSTS`. Please note, that the behaviour of `manage.py` changed: It now uses the settings in `development.py` automatically, while `[project_root]/wsgi.py` refers to the settings in `production.py`.

2.3.5 djangodefault.py

(removed in 1.2) This are the saved settings from `django-admin startproject`. We just keep them for completeness, these settings are not actually used.

2.4 Apache2 Virtual Host Configuration

This is an Apache2 configuration file for name based virtual hosting.

As you can see in the following listing, there are several placeholders, that must be filled to make this work.

2.4.1 Usage

As you may notice, there are three different types of placeholders.

[[placeholder_name]] These placeholders must be filled manually. Most noticable is line 4, where you **must** set the server name.

```
ServerName [[SERVER_NAME]]
```

\${placeholder_name} These placeholders are filled by Apache itself. Only mess with them, if you do exactly know what you are doing.

{{ placeholder_name }} These placeholders do look familiar, don't they? These are Django templatetags. You may fill them manually (please refer to the provided resources in the comments), but you can Django let them fill them for you during project creation. This will render the file through Django's template engine and fill these placeholders:


```
$ django-admin startproject --template=/path/to/template --name apache2_vhost.
↪sample
```

2.4.2 Concept

This will set up a name based virtual host that uses *mod_wsgi* to interact with Django.

It will serve static- and media-files from the default locations set in `settings/common.py`. This is not a production-setting, but is well suited for development purposes.

Line 10: Alias /static/ {{ project_directory }}/run/static Serve static files from `STATIC_ROOT` under `STATIC_URL`. Note lines 36 - 40, where the directory is made accessible for Apache.

Line 15: Alias /media/ {{ project_directory }}/run/media Serve media files from `MEDIA_ROOT` under `MEDIA_URL`. Note lines 45 - 49, where the directory is made accessible for Apache.

The dynamic Django content is served using the *WSGI-application*. Apache2 will use *mod_wsgi* in Daemon-mode. This is in fact the preferred way of deploying Django with Apache2, so you will not have to mess with these settings.

Line 18: WSGIScriptAlias / {{ project_directory }}/{{ project_name }}/wsgi.py This must be set to the absolute filesystem path to the *WSGI-application*.

Line 27: WSGIDaemonProcess ... This sets the name of the daemon process. Using Django's template engine, this will be set to the name of your project. Please notice the `python-path`-parameter. It is prepared to a virtualenv-setup, but frankly, it must contain the *project directory* and the path to Python's *site-packages*.

Line 31: WSGIProcessGroup ... Specifies a distinct name for the daemon process's group.

2.4.3 Source

```
1 <VirtualHost *:80>
2     # This is name based virtual hosting. So place an appropriate server name
3     # here. Example: django.devsrv.local
4     ServerName [[SERVER_NAME]]
5     ServerAdmin webmaster@localhost
6
7     # This alias makes serving static files possible.
8     # Please note, that this is geared to our settings/common.py
9     # In production environment, you will probably adjust this!
10    Alias /static/ {{ project_directory }}/run/static/
11
12    # This alias makes serving media files possible.
13    # Please note, that this is geared to our settings/common.py
14    # In production environment, you will probably adjust this!
15    Alias /media/ {{ project_directory }}/run/media/
16
17    # Insert the full path to the wsgi.py-file here
18    WSGIScriptAlias / {{ project_directory }}/{{ project_name }}/wsgi.py
19
20    # PROCESS_NAME specifies a distinct name of this process
21    # see: https://code.google.com/p/modwsgi/wiki/ConfigurationDirectives
22    ↪#WSGIDaemonProcess
23    # PATH/TO/PROJECT_ROOT is the full path to your project's root directory,
24    # containing your project files
25    # PATH/TO/VIRTUALENV/ROOT: If you are using a virtualenv specify the full
```

```

25 # path to its directory.
26 # Generally you must specify the path to Python's site-packages.
27 WSGIDaemonProcess {{ project_name }} python-path={{ project_directory }}:{{ _
↳project_directory }}/../lib/python2.7/site-packages
28
29 # PROCESS_GROUP specifies a distinct name for the process group
30 # see: https://code.google.com/p/modwsgi/wiki/ConfigurationDirectives
↳#WSGIProcessGroup
31 WSGIProcessGroup {{ project_name }}
32
33 # Serving static files from this directory
34 # Please note, that this is geared to our settings/common.py
35 # In production environment, you will probably adjust this!
36 <Directory {{ project_directory }}/run/static>
37     Options -Indexes
38     Order deny,allow
39     Allow from all
40 </Directory>
41
42 # Serving media files from this directory
43 # Please note, that this is geared to our settings/common.py
44 # In production environment, you will probably adjust this!
45 <Directory {{ project_directory }}/run/media>
46     Options -Indexes
47     Order deny,allow
48     Allow from all
49 </Directory>
50
51 LogLevel warn
52
53 # PROJECT_NAME is used to separate the log files of this application
54 ErrorLog {{APACHE_LOG_DIR}}/{{ project_name }}_error.log
55 CustomLog {{APACHE_LOG_DIR}}/{{ project_name }}_access.log combined
56 </VirtualHost>

```

2.5 Versions

1.3, master suitable for Django version: 1.11:

```

$ django-admin startproject --template=https://github.com/Mischback/django-
↳project-skeleton/archive/1.3.zip [projectname]

```

1.2 suitable for Django version: 1.11:

```

$ django-admin startproject --template=https://github.com/Mischback/django-
↳project-skeleton/archive/1.2.zip [projectname]

```

1.1 suitable for Django version: 1.8:

```

$ django-admin startproject --template=https://github.com/Mischback/django-
↳project-skeleton/archive/1.1.zip [projectname]

```

1.0 suitable for Django version: 1.7.4:

```
$ django-admin startproject --template=https://github.com/Mischback/django-  
↳project-skeleton/archive/1.0.zip [projectname]
```

This is the initial release, development reflects the Django version 1.7.4. Should be suitable for most versions of release 1.7, but please be aware that only 1.7.4 is tested.

CHAPTER 3

Hall of Fame

It's been a while, I even missed some Django-releases completely. Some guys at Github picked up the project and made some changes to keep it in line with Django-releases. I grabbed some code from the, so they are considered *Contributors* to this project and should be mentioned here:

- [agirardeaudale](#)
- [jmrbcu](#)